

Multiple screen sizes

Choose the perfect fit for your space with 320mm and 480mm wide panels.









The entire cabinet is IP66-rated on both the front and rear, certified by TUV, ensuring complete protection against water ingress. Its fanless cooling system prevents dust and dirt from entering, helping to extend the lifespan of the internal electronic components.




Simple and strong aluminum back frame

The LED panel is supported by a robust, streamlined aluminum back frame that mounts directly to the wall, ensuring a secure and seamless installation. This durable, lightweight design provides long-term stability while maintaining a sleek, low-profile appearance..











High Brightness

No matter the environment, high brightness matters for delivering flawless image clarity and maintaining superior picture quality, even in well-lit spaces or direct sunlight.





Slim and light weight design

Position Pins

Position pin on the cabinets are easy to locate into the frame.

Handles

Handles on the top are easy to pull the cabinet up with safety wire.





Specifications

ATS-PRO Element Ribbon Series LED panel shown.

Pixel Pitch (mm) 3.91 5.71 6.67 8 10 Panel Dimensions (W*H*D)/(mm) 750*750 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 960*960 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30<	Specifications	RB3.9	RB5.7	RB6.6	RB8	RB10
Panel Dimensions (W'H'D)/(mm) 750*750 960*960 960*960 960*960 960*960 Pixel Per Panel (w, h) 192X192 168X168 144X144 120X120 96X96 Panel Weight (kg/m²) 30 30 30 30 30 30 Panel Material Aluminum 3.840	LED Type	SMD1921 GOLD OR COPPER	SMD2727 GOLD OR COPPER	SMD2727 GOLD OR COPPER	SMD3535 GOLD OR COPPER	SMD3535 GOLD OR COPPER
Pixel Per Panel (w, h) 192X192 168X168 144X144 120X120 96X96 Panel Weight (kg/m²) 30 30 30 30 30 30 Panel Material Aluminum	Pixel Pitch (mm)	3.91	5.71	6.67	8	10
Panel Weight (kg/m²) 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 30 3840 3840 3840 3840 3840 3840 3840 3840 3840 3840 3840 384	Panel Dimensions (W*H*D)/(mm)	750*750	960*960	960*960	960*960	960*960
Panel Material Aluminum	Pixel Per Panel (w, h)	192X192	168X168	144X144	120X120	96X96
Module Dimensions (W*H)/(mm) 375x250 480x320 480x320 480x320 480x320 480x320 480x320 480x320 480x320 480x320 10,000 10,000 10,000 10,000 10,000 10,000 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840	Panel Weight (kg/m²)	30	30	30	30	30
Brightness (nit) 7,000 9,000 10,000 10,000 10,000 Refresh Rate (Hz) 3,840 3,840 3,840 3,840 3,840 3,840 Grayscale (bit) 14-16 bit 16-16 b	Panel Material	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Refresh Rate (Hz) 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840 3,840	Module Dimensions (W*H)/(mm)	375x250	480x320	480x320	480x320	480x320
Grayscale (bit) 14-16 bit 15-16 bit 15-16 bit 15-16 bit 15-16 bit 15-16 bit 15-16 bit 14-16 bit 15-16 bit 15-16 bit 16-16 bit 15-16 bit 16-16 bit	Brightness (nit)	7,000	9,000	10,000	10,000	10,000
Power Consumption (Max./Avg.) (W/m²) 570/171 580/174 580/174 550/165 550/165 IP Rating (Front/Rear) IP66/IP66 IP6	Refresh Rate (Hz)	3,840	3,840	3,840	3,840	3,840
IP Rating (Front/Rear) IP66/IP66 IP66/IP66 <td>Grayscale (bit)</td> <td>14-16 bit</td> <td>14-16 bit</td> <td>14-16 bit</td> <td>14-16 bit</td> <td>14-16 bit</td>	Grayscale (bit)	14-16 bit				
Module Maintenance Top Top Top Top Top Top PSU & Others Maintenance Top Top Top Top	Power Consumption (Max./Avg.) (W/m²)	570/171	580/174	580/174	550/165	550/165
PSU & Others Maintenance Top Top Top Top Top	IP Rating (Front/Rear)	IP66/IP66	IP66/IP66	IP66/IP66	IP66/IP66	IP66/IP66
	Module Maintenance	Тор	Тор	Тор	Тор	Тор
Panel Installation Type Front Front Front Front Front	PSU & Others Maintenance	Тор	Тор	Тор	Тор	Тор
	Panel Installation Type	Front	Front	Front	Front	Front

Specifications subject to change. Please contact ATS-Pro for updated specifications.





Masters in the Art of LED

©2025 ATS PRO. ATS PRO is a registered mark of Activate the Space, LLC. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. Simulated screen images. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. See ats-pro.com for detailed information.

www.ats-pro.com | 800-755-3235









in O () @atsproled