

# Poster LED Series



Portable. Self Contained.  
Free Standing LED Monolith.

POSTER LED SERIES 2.5mm



## Ultra-Slim & Light Design

The front frame thickness has only a 1.5 mm Bezel. When Poster LED's are placed side by side it is only a 3M Bezel that is created, making it nearly invisible. The high-end aluminum frame and slim design makes the appearance of the Poster LED simple and impactful. The base is equipped with wheels allowing the Poster LED to be moved easily by one person, making relocation simple and easy.



### Multi Screen Splicing

Multi-screen cascade brings a unique visual experience supporting both single-screen and split-screen mode for up to 6 units.



### Up to 4K Resolution

With the addition of an external video wall processor, 10-16 units can be synced together for up to 4K horizontal resolution.



### Multiple Customer Uses

Perfect for use in Commercial Facilities, Offices, Education, Shopping Malls, Clubs, Hotels, Airports, Restaurants, Supermarkets, Showrooms, Exhibitions, Weddings, and Events.



### Wifi

Has a Built-in Media Player that is supported by PC & Android Apps. In addition, it is equipped with Wifi, providing support via your mobile device, including content publishing.



### HDMI

For those that want to use their own Media Playback system, included is an external HDMI input allowing you to use any digital signage software that you choose.



### USB

You can also simply plug a USB Thumb drive to play content directly to the Poster LED.



### Free Standing Case Included

Folds easily for relocating your Poster LED as well as making the corrugated shipping packaging small.



### Optional Wall Mount

Remove the base and add the wall mounting bracket to easily hang on any wall surface or fixture. Landscape or Portrait brackets available.



### Optional Road Case

Single and Double ATA Road Cases available.



# Specifications

ATS-PRO Poster LED Series.

Specifications	Poster LED 2.5
Pixel Pitch (mm)	2.5 mm
Module Size	160 x 160mm
Module Pixel	64 x 64
Module Resolution	4096 dots
Screen Size	640 x 1920mm
Screen Resolution	256 x 768
Frame Size	644 x 1930mm / 25.35" x 76"
Screen Thickness	45mm / 1.77"
Brightness	≥1,100 CD/m <sup>2</sup>
Screen Weight	38kg / unit / 83.78 lbs
Case Material	Aluminum
Operating Temperature Range	-10°C to + 70°C
Pixel Type (R/G/B)	SMD3 in 1
Grayscale	16 bits RGB
Video Frame Rate	60 Hz
Refresh Rate	>1,200 Hz
Input Voltage	AC90-240V
Maximum Input Power	600W
Minimum Input Power	280W
Software	HD Player
Control	USB / WIFI / Lan / HDMI
Use Scenario	Indoor
Panel Installation Type	Floor / Wall (Landscape or Portrait)

Specifications subject to change. Please contact ATS-Pro for updated specifications.

**Learn More**

[ats-pro.com](https://ats-pro.com)

**Contact Us**

1-800-755-3235

**Follow Us**

[in linkedin.com/company/atsproled](https://www.linkedin.com/company/atsproled)
[instagram.com/atsproled](https://www.instagram.com/atsproled)
[facebook.com/atsproled](https://www.facebook.com/atsproled)
[@ATSPRO5](https://twitter.com/ATSPRO5)

